



Die in der Tabelle angegebenen Stützweiten dienen als schnelle Bemessungshilfe für eine überschlägige Vorbemessung von Brettschichtholz.

Elastizitätsmodul: 11000 N/mm²
 Durchbiegung: L/300
 Festigkeitsklasse: GL 24h
 Brandwiderstand: F30



Belastung kN/m	2,0	3,0	4,0	5,0	6,0	7,0	8,0	9,0	10,0	11,0	12,0	
Stützweite/m												
	1,0	6/12	6/12	6/12	6/12	6/14	6/14	6/14	6/14	6/14	6/16	6/16
2,0		8/10	8/10	8/10	8/10	8/10	8/10	8/10	8/12	8/12	8/12	8/12
		6/14	6/16	6/18	6/20	8/16	8/18	8/18	8/20	8/20	8/20	8/22
3,0		8/10	8/12	8/14	8/16	10/14	10/14	10/16	10/16	10/18	10/18	10/20
		10/10	10/12	10/12	10/12	12/12	12/14	12/14	12/16	12/16	12/16	12/18
		6/20	8/18	8/20	8/22	8/22	8/24	10/24	10/24	10/26	10/26	10/28
4,0		8/16	10/16	10/18	10/18	10/20	10/22	12/22	12/22	12/24	12/24	12/26
		10/14	12/16	12/16	12/18	12/18	12/20	12/20	14/20	14/20	14/22	14/24
		12/14	14/14	14/16	14/18	14/18	14/18	16/18	16/20	16/20	16/22	16/22
		8/20	8/22	8/24	10/24	10/26	10/28	12/28	12/30	12/32	12/32	12/36
5,0		10/18	10/22	10/24	12/24	12/24	12/26	14/28	14/28	14/28	14/30	14/32
		12/18	12/20	12/22	14/22	14/24	14/24	16/24	16/26	16/28	16/28	16/30
		14/16	14/20	14/20	16/22	16/22	16/24	18/24	18/24	18/26	18/26	18/28
		8/24	10/26	10/28	12/30	12/30	12/32	12/36	12/36	14/40	12/40	14/40
		10/24	12/24	12/28	14/28	14/30	14/30	14/32	14/36	14/36	14/40	16/36
6,0		12/22	14/24	14/26	16/26	16/28	16/30	16/30	16/32	16/36	16/36	18/36
		14/20	16/22	16/24	18/26	18/28	18/28	18/30	18/30	18/32	18/36	20/32
		10/28	12/30	12/32	12/36	12/36	12/40	14/40	14/40	16/40	16/44	16/44
		16/26	14/28	14/30	14/36	14/36	14/36	16/36	16/40	18/40	18/40	18/44
7,0		14/24	16/26	16/30	16/32	16/36	16/36	18/36	18/36	20/36	20/40	20/40
		16/24	18/26	18/28	18/30	18/32	18/36	20/36	20/36			
		12/30	12/36	12/40	12/40	14/40	16/40	16/44	16/44	18/44	20/44	
		14/28	14/32	14/36	14/40	16/40	18/40	18/44	18/44	20/44		
8,0		16/28	16/32	16/36	16/36	18/40	20/40	20/40	20/44			
		18/26	18/30	18/32	18/36	20/36						
		12/36	12/40	14/40	16/44	16/44	18/44					
		14/32	14/40	16/40	18/40	18/44	20/44					
9,0		16/32	16/36	18/40	20/40	20/44						
		18/30	20/32	20/36								
		12/40	16/40	16/44	20/44							
10,0		14/36	18/40	18/44								
		20/32	20/36	20/40								
		14/40	16/44									
	16/40	18/44										
	20/36	20/40										

Diese Vorbemessungen ersetzen nicht die statische Berechnung im Einzelfall.
 Kippsicherheit wurde nicht durchgeführt! Fehler können wir trotz aller Sorgfalt nicht ausschließen.
 Irrtum bleibt vorbehalten.